



SmartRail X100-MID - Summary Sheet

Summary

The X100 is the smallest 100 Amp meter on the market. The compact shell comes with a variety of features, which include a partial counter reset button and recording of both Import and Export Energy .

The range of parameters that this meter records are; Active Energy (kWh) including Total, Import & Export, Reactive Energy (kVAh) including Total, Import & Export, Voltage (V), Current, (I), Active Power (kW), Reactive Power (kVAr), Apparent Power (kVA), Power Factor (PF), Power Max Demand (MD kW) and Frequency (Hz).

The X100 has an RS485 Modbus RTU for connection to a BMS system and it incorporates 2 pulsed outputs which are proportional to active and reactive energy.

N.B. This meter can be fitted into a DIN Rail enclosure. [Click here](#) to see our full range of Enclosures.

Product Code


Meter Type
Fitting Type
Max Current (Amps)
MID Approved
Smart
Input Type
Output Type

Tariffs
Import / Export
Module Width
Availability
Condition
Brand
Country of Manufacture


SPDX100M

Single Phase
DIN Rail
100
Yes
No
Direct Connect
RS485 Modbus & Pulse
Single
Import & Export
2
Next Day
New
Smart Process
China

Dimensions



Wiring Diagram



Web: www.spwales.com | Email: sales@spwales.com | Phone: 01803 295430 | Fax: 01803 212819

While Stephen P Wales Ltd has made every reasonable effort to ensure the accuracy of this information, Stephen P Wales Ltd does not guarantee that it is error-free, nor does Stephen P Wales Ltd make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. Stephen P Wales Ltd reserves the right to make any adjustments to the information contained herein at any time without notice.